



See nothing, hear everything

The CCM7.4 features 2 x 130mm(5in) bass/mid-range Kevlar® drivers set in a die-cast chassis and a Nautilus $^{\text{TM}}$ tube loaded 25mm (1in) soft dome tweeter. Its critically formed baffle is constructed from glass reinforced ABS. The baffle features a scallop under the tweeter which creates the perfect roll off for high frequencies resulting in a more accurate reproduction of sound.

Technical Specifications

Description 2-way in-ceiling system

Drive Units 1x Ø25mm (1in) Nautilus™ tube loaded soft dome tweeter

2x ø130mm (5in) blue Kevlar® cone bass/midrange

Frequency Range (-6dB) 52Hz – 28kHz **Recommended Amp Power** 25 - 150w Sensitivity SPL (2.83V, 1m) 88.5 dB 8Ω (6.5Ω) Impedance Nominal (min) Frame height 355mm (14in) Frame width 355mm (14in) **Cut-out height** 332mm (13.1in) **Cut-out width** 332mm (13.1in) Depth behind surface 184mm (7.2in) **Protrusion** 6.5mm (0.25in)

7C

PMK

Bowers & Wilkins

www.bowers-wilkins.com

Nautilus, Flowport and FST are trademarks of B&W Group Ltd.
Kevlar is a registered trademark of DuPont. Copyright © B&W Group Ltd. E&OE

