



See nothing, hear everything

The CWM7.4 features a 150mm (6in) bass/mid-range driver set in a die-cast chassis and a Nautilus[™] tube loaded 25mm (1in) soft dome tweeter. With a critically formed baffle constructed from glass reinforced ABS, the speaker features a scallop under the tweeter which creates the perfect roll off for high frequencies resulting in a more accurate reproduction of sound. Utilising the best quality components, such as having Mundorf components on the crossover, combined with proven technologies such as Flowport[™] ensures that this speaker provides impressive sound reproduction.

Technical Specifications

Description 2-way in-wall system

Drive units 1x ø25mm (1in) Nautilus™ tube loaded soft dome tweeter

1x Ø150mm (6in) blue Kevlar® cone bass/midrange

Frequency Range (-6dB)47Hz - 28kHzRecommended Amp Power25 - 150wSensitivity SPL (2.83V, 1m)89dBImpedance Nominal (min)6Ω (5Ω)

415mm (16.5in) Frame height 251mm (10in) Frame width **Cut-out height** 390mm (15.4in) **Cut-out width** 226mm (8.9in) Cut-out height w/PMK 395mm (15.6in) Cut-out width w/PMK 232mm (9.1in) 102mm (4.in) Depth behind surface Reservoir box height 460mm (18.1in) Reservoir box width 220mm (8.7in) Reservoir box depth 60mm (2.4in) 8mm (0.32in) Protrusion 7.4W **PMK**

Bowers & Wilkins

www.bowers-wilkins.com

Nautilus, Flowport and FST are trademarks of B&W Group Ltd.
Kevlar is a registered trademark of DuPont. Copyright © B&W Group Ltd. E&OE

