



See nothing, hear everything

The CWM7.5 contains a 130mm(5in) bass/mid-range Kevlar® driver set in a die-cast chassis and a Nautilus™ tube loaded 25mm (1in) soft dome tweeter. Utilising proven technologies such as Flowport™ the speaker also features the best quality components such as having Mundorf components on the crossover. It has a critically formed baffle constructed from glass reinforced ABS and the extra-rigidity provides a much cleaner sound reproduction.

Technical Specifications

Description	2-way in-wall system
Drive units	1x ø25mm (1in) Nautilus™ tube loaded soft dome tweeter 1x ø130mm (5in) blue Kevlar® cone bass/midrange
Frequency Range (-6dB)	49Hz – 28kHz
Recommended Amp Power	25 – 150w
Sensitivity SPL (2.83V, 1m)	86dB
Impedance Nominal (min)	6Ω (5.2Ω)
Frame height	356mm (14in)
Frame width	212mm (8.5in)
Cut-out height	331mm (13in)
Cut-out width	187mm (7.4in)
Cut-out height w/PMK	336mm (13.2in)
Cut-out width w/PMK	192mm (7.6in)
Depth behind surface	102mm (4.02in)
Reservoir box height	385mm (15.2in)
Reservoir box width	181mm (7.1in)
Reservoir box depth	60mm (2.4in)
Protrusion	8mm (0.32in)
PMK	7.5W